



FCA5050

Die cast aluminum
post top



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCA5050	120V - 277V	PL: 26T 42T HID: 50MH 70MH 100MH	BK Black BZ Bronze CC Custom Color SL Silver WH White	347V Voltage D Dimming EC E-coat (use for coastal /severe wheather areas) F Fuse EMR Emergency backup remote (PL Only, 12ft. max all EMRs) F Fuse LP Pole length (please indicate 79", 99", 118", 138" or 158") OP Opal diffuser

Product Information

Listing: UL & cUL listed for wet locations. IP 67 rated.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum and extruded aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, UV stabilized, opal, polycarbonate diffuser.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. HID: Medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Remote electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coast comes with a 5 year warranty.

Mounting: Pole sold separately. See pages 144-147. Fixture mounts to pole with 4-1/8" max diameter x 2-3/4" long tenon.

