



FCA5110PMA

Die cast aluminum
post top



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCA5110PMA	120V - 277V	70MH	BK Black	EC E-coat (use for coastal /severe weather areas)
FCA5110PMA2		150MH	BZ Bronze	F Fuse
			CC Custom	347V Voltage
			SL Silver	
			WH White	

Product Information

Listing: UL & cUL listed for wet locations. IP 67 rated.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum and extruded aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, UV stabilized, prismatic polycarbonate.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.


Socket: HID: Medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

Ballast: HID: Electronic ballast standard. Remote ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting: Pole sold separately. See pages 144-147. Fixture mounts to pole with 2-3/8" tenon.

FCA5110PMA



FCA5110PMA2

