




FCA5500

Die cast aluminum
linear post



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCA5500	120V - 277V	3 / 28T5 3 / 32T8	BK Black BZ Bronze CC Custom Color SL Silver WH White	D Dimming EC E-coat (use for coastal /severe wheather areas) 347V Voltage

Product Information

Listing: UL & cUL listed for wet locations. IP 65 rated.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast arm and fixture base. Secondary reflector panel is reinforced fiber with die cast aluminum support arm.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, UV stabilized, opal, polycarbonate diffuser.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.

Socket: PL: Two pin plug-in type fluorescent lamp holder (lamp by others). Holder assures precise optical alignment.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Pole: Sold separately.

