



## FCA719

Die cast aluminum  
linear post



corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

### Catalog Number

Series	Voltage	Source/Wattage	Finish	Accessories
FCA719	120V - 277V	39MH G12 70MH G12 150MH G12	<b>BK</b> Black <b>BZ</b> Bronze <b>CC</b> Custom Color <b>SL</b> Silver <b>WH</b> White	<b>EC</b> E-coat (use for coastal /severe weather areas)

### Product Information

**Listing:** UL & cUL listed for wet locations.

**Construction:** Marine grade, corrosion resistant, heavy gauge die cast aluminum with extruded pole. Easy access maintenance.

**Gasket:** Neoprene continuous closed cell gasket to seal out contaminants.

**Fasteners:** Captive and recessed stainless steel, tamper resistant hex socket screws.

**Diffuser:** Impact resistant, UV stabilized, clear, acrylic diffuser.

**Socket:** HID: Medium base pulse rated 4KV porcelain socket or G12 base. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

**Ballast:** HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

**Mounting:** A .50" thick die cast base plate is provided and anchored through with a set of four 12" in length x .5" diameter hot dipped anchor bolts.

