



## FCC914PMA

9" Die cast aluminum square cylinder



corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

### Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCC914PMA FCC914PMA2	120V - 277V	PL: 26T, 42T INC: 200W A21 HID: 39MH G12 70MH G12 50MH 70MH 100MH LED: 10W 20W	BK Black BZ Bronze CC Custom Color SL Silver WH White	D Dimming (consult factory) EC E-coat (use for coastal /severe wheather areas) F Fuse EMR Emergency backup remote (PL only 12ft max) QR Quartz restrike 347V Voltage

### Product Information

**Listing:** UL & cUL listed for wet locations.

**Construction:** Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction with die cast back mounting plate.

**Gasket:** Neoprene continuous closed cell gasket to seal out contaminants.

**Diffuser:** Lens is heat resistant, clear, tempered glass.

**Reflector:** Precision spun/formed aluminum, anodized specular clear for maximum reflectance.

**Socket:** PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. INC: (120V only) Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating. HID: G12 base porcelain socket and double silicone jacket wire with a 200°C rating.

**LED:** Integral inverter and driver potted with a variable input of voltage from 120V to 240V. Consult factory for color changing or multi-color combinations and other voltage options.

**Ballast:** PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

**Mounting:** Pole sold separately. See pages 144-147.

