



FCW Series

Exterior / Interior
architectural triangular
post top



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCW1040PMA	120V - 277V	PL: 26Q, 32T, 42T, 57T, 70T INC: 150W R7s, 250W R7s, 300W R7s HID: 39MH G12, 70MH G12, 150MH G12 LED: 20W 60W	BK Black BZ Bronze CC Custom Color SL Silver WH White	D Dimming (PL only) EC E-coat (use for coastal /severe weather areas) EMR Emergency back-up remote (PL only, 12ft. max) F Fuse PE Photo Eye QR Quartz restrike 347V Voltage

Product Information

Listing: UL & cUL listed for wet locations.

Construction: Corrosion resistant, heavy walled, solid cast aluminum construction.

Gasket: Extruded silicone to provide maximum protection against contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant hex socket screws.

Diffuser: Lens is 1/8" thick tempered, clear, heat resistant.

Reflector: Precision formed semi-specular aluminum for maximum reflectance (FCW1040PMA).

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. INC: (120V only) R7s double ended base. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating. HID: G12 base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

LED: Integral inverter and driver potted with a variable input of voltage from 120V to 240V. Consult factory for color changing or multi-color combinations and other voltage options.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting: Pole sold separately. See pages 144-147.

Front View

Side View

