



FCW Series

Exterior architectural decorative die cast aluminum wall mount



Architectural

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCW4106PMA	120V - 277V	PL: 13Q 26T 32T 42T INC: 100W A19 HID: 39MH G12 50MH 70MH 70MH G12	BK Black BZ Bronze CC Custom Color SL Silver WH White	EC E-coat (use for coastal /severe weather areas) EMR Emergency back, remote (PL only, 12ft max all EMRs) F Fuse PE Photo eye 347V (Consult factory)

Product Information

Listing: UL & cUL listed for wet locations.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant hex socket screws.

Diffuser: Impact resistant UV stabilized stipple frosted diffuser globe. (Glass lens enclosure for HID only.)

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. INC: (120V only) Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating. HID: Medium or G12 base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting: Pole sold separately. See pages 144-147.

