


## FCW Series

Exterior die cast aluminum  
exterior wall, pier or pole  
mount with guard



### Catalog Number

Series	Voltage		Source/Wattage	Ballast	Finish	Accessories
FCW5001PMA	120V	18Q	100W A19 INC 50MH	E Electronic	BK Black	DL Directional Louver
FCW5002PMA	277V	26Q	200W A21 INC 70MH	M Magnetic	BZ Bronze	EC E-Coat
	347V	26T	100MH		SL Silver	EMR Emergency Back-up, remote (PL only)
	(Canada)	32T			WH White	F Fuse
		42T			CC Custom Color	LRI Long Range Ignitor
		57T				RO Remote outdoor ballast box
		70T				347V Voltage (consult factory)
						Q Quartz restike (▶HID integral ballast only)

### Product Information

**Listing:** UL & cUL listed for wet locations.

**Construction:** Marine grade corrosion resistant, heavy walled, high pressure die cast aluminum construction.

**Gasket:** Extruded silicone to provide maximum protection against contaminants.

**Fasteners:** Captive stainless steel, tamper resistant hex socket screws.

**Diffuser:** Impact resistant, UV stabilized, opal, polycarbonate diffuser.

**Socket:** PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating. **HID:** Medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating (**lamps by others**).

**Ballast:** PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120-277V is standard. Please consult factory for other voltage options.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-Coat process added to standard finish including zinc phosphate.

**Mounting:** Pole sold separately. Fixture mounts to pole with 2 3/8" tenon.

FCW5001PMA



FCW5002PMA

