



Type:	Approved:
Fixture:	
Project:	

## FCB1235 Series

Die cast aluminum bollard



### Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCB1235	120V-277V	PL: 26T HID: 39MH G12 70MH G12	BL Black BZ Bronze CC Custom Color SL Silver WH White	EC E-Coat F Fuse OD Opal Diffuser 347V Voltage

### Product Information

**Listing:** UL and cUL listed for wet location. IP 65 rated.

**Construction:** Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction. Tubular housing is extruded aluminum.

**Gasket:** Neoprene continuous closed cell gasket to seal out contaminants.

**Fasteners:** Hidden fasteners allow for cover removal to facilitate installation and service.

**Diffuser:** Impact resistant, UV stabilized, clear, prismatic polycarbonate.

**Reflector:** Precision formed semi-specular aluminum for maximum reflectance.

**Socket:** **PL:** Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **HID:** G12 base porcelain socket and double silicone jacket wire with a 200°C rating.

**Ballast:** **PL:** Fluorescent high power factor electronic, UL listed ballast standard. **HID:** electronic ballast standard. Ballast is thermally protected and is rated HPF > 90%, THD < 10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120-277V is standard. Please consult factory for other voltage options.

**Finish:** Seven stage preparation process that includes TGIC super polyester powder-coat is standard. Optional E-Coat process added to standard finish including zinc phosphate.

**Anchoring:** A thick die cast base plate is provided and anchored through with a set of (4) four 12" length x 3/8" diameter hot dipped anchored bolts. Heavy gauge base bracketing for bollard installation.

### Product Dimensions

