



corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

## FCB Series

Die cast aluminum  
bollard

New!



### Catalog Number

Series	Voltage	Source/Wattage	Ballast	Finish	Accessories
FCB840	120V	39MH G12	E Electronic	BK Black	EC E-coat
FCB841	277V	70MH G12	M Magnetic	WH White CC Custom Color	F Fuse PE Photo eye

### Product Information

**Listing:** U.L. listed for wet locations.

**Housing & Guard:** Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction. Tubular housing is extruded aluminum.

**Gasket:** Neoprene continuous closed cell gasket to seal out contaminants.

**Fasteners:** Captive and recessed stainless steel, tamper resistant, hex socket screws.

**Diffuser:** Lens is tempered clear glass.

**Reflector:** Precision formed semi-specular aluminum formed for maximum reflectance.

**Socket:** G12 base porcelain socket, and double silicone jacket wire with a 200°C rating.

**Ballast:** Dual voltage (120/277) core and coil, high power factor, thermally protected ballast, standard. Electronic ballast available.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

**Anchoring:** A .125" thick base plate is provided and anchored through with a set of three 12" in length hot-dipped anchor bolts. Heavy gauge base bracketing for bollard installation.

