



Type:	Approved:
Fixture:	
Project:	

FCB Series

Exterior die cast architectural bollard



Catalog Number

Series	Voltage	Source / Wattage	Ballast	Finish	Accessories
FCB89	120V	39MH	E Electronic	BL Black	EC E-Coat
	277V	70MH		BZ Bronze	F Fuse
	347V			CC Custom Color	DP160 160° Distribution
			SL Silver	DP2x80 2 x 80° Distribution	
			WH White	DP360 360° Distribution	

Product Information

Listing: UL and cUL listed for wet location. IP 65 rated.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Lens is heat resistant, vandal proof polycarbonate.

Socket: HID: G12 base porcelain socket and double silicone jacket wire with a 200°C rating.

Ballast: HID: Electronic ballast standard. Ballast is thermally protected and rated HPF > 90% THD < 10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V - 277V is standard. Please consult factory for other voltage options.

Finish: Seven stage preparation process that includes TGIC super polyester powder-coat is standard. Optional E-Coat process added to standard finish including zinc phosphate.

Mounting: A thick die cast base plate is provided and anchored through with a set of (4) four 12" length x 3/8" diameter hot dipped anchored bolts. Heavy gauge base bracketing for bollard installation.

Product Dimensions

