

FCC Series

14" Cylinder surface,
pendant or wall mount



Cylinder

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Source/Wattage	Ballast	Finish	Accessories
FCC1424	Surface	120V 32T 100INC	E Electronic	BK Black	C Clear lens
FCC1424W	Wall	277V 42T 200INC	M Magnetic	BA Brushed aluminum	D Dimming (PL only)
FCC1424P	Pendant	347V 57T 250WQ T4 (Canada) 70T 500W Par56		WH White	EC E-coat
				CC Custom color	EMR Emergency back up (PL only)
					F Fuse
					P Prismatic Lens
					PDT Pendant mount (specify length, 48" standard)
					Q Quartz restrike (HID integral ballast only)
					SC Safety chain (for lens)
					SWC Swivel canopy
		150MH 200MH 250MH 320MH 400MH 150HPS 250HPS 400HPS			

▷Recommended lamping
◁250W Max.

▶not available with 277V or 347V electronic ballast

Product Information

Listings: U.L. listed for damp locations.

Housing: Corrosion resistant heavy gauge aluminum.

Diffuser: Lens is heat resistant, clear tempered glass, standard metal halide (MH) only.

Reflector: Heavy gauge aluminum reflector with clear specular Alzak® finish cone.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact. Mini cand for T4. **HID:** Medium /mogul (250 & higher) base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact. Both incandescent and HID have double silicone jacket wire with a 200°C rating.

Ballast: PL: Fluorescent high power factor electronic, U.L. listed ballast standard. **HID:** Dual voltage (120/277) core and coil, high power factor, thermally protected ballast, standard.

Mounting: Mounts directly to standard recessed junction box. Optional pendant mount (18" standard) and wall mount applications are available.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Options: Pendant mount optional, 18" length is standard. **PL:** Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only.

