



| | |
|----------|-----------|
| Type: | Approved: |
| Fixture: | |
| Project: | |

FCC Series

6" die cast aluminum up or down light, wall mount cylinder



Catalog Number

| Series | Voltage | | Source/ Wattage | | 18W LED | Finish | Accessories |
|------------------------------------|-------------------------|-----|-----------------|-------------|---------|-----------------|---|
| FCC618W <i>(up / down wall)</i> | 120V | 13Q | 75W PAR 30L | 39MH PAR 20 | | BK Black | EC E-Coat |
| | 277V | 18T | 150W PAR 38 | 20MH T4.5 | | WH White | EMR Emergency Backup, Remote <i>(PL Only)</i> |
| | 347V <i>(Canada)</i> | 26T | | 39MH G12 | | CC Custom Color | F Fuse |
| | | 32T | | | | | D Dimming <i>(Consult Factory)</i> |
| | | | | | | | TLV Turbo Louver |

Product Information

| | |
|------------------|--|
| Listing | UL listed for wet locations. IP 65. |
| Housing | Marine grade, corrosion resistant, heavy walled, high pressure, die cast aluminum construction with die-cast back mounting plate and extruded aluminum body. |
| Baffle | Die cast aluminum baffle in fixture color unless otherwise specified. |
| Gasket | Neoprene continuous closed cell gasket to seal out contaminants |
| Fasteners | Hidden fasteners allow for cover removal to facilitate installation and service. |
| Reflector | Precision formed semi-specular aluminum formed for maximum reflectance. |
| Socket | PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. INC (120V only) / PAR HID: Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating (lamps by others). HID: G12 base for 39MH and G8.5E base for 20MH. |
| Ballast | PL: Fluorescent high power factor electronic, UL listed ballast, standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a 5 year manufacturers warranty. |
| Finish | Seven stage preparation process that includes TGIC super polyester powder-coat is standard. Optional E-Coat process added to standard finish including zinc phosphate. |
| Mounting | Mounts directly to standard outlet box. |
| Options | PL: Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only. |

Product Dimensions

