



corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

## FCC Series

Large diameter die cast aluminum down light surface or pendant mount cylinder



### Catalog Number

Series	Voltage	Wattage	Ballast	Finish	Accessories
FCC813 surface	120V	26T 90W Par 38 70MH G12◀	E Electronic	BK Black	D Dimming (PL only)
FCC813P pendant	277V 347V (Canada)	32T 150W Par 38 42T		WH White CC Custom color	EC E-coat EMR Emergency back-up, remote (PL only) F Fuse

### Product Information

**Listing:** U.L. listed for wet location in down position.

**Housing:** Marine grade corrosion resistant heavy wall high pressure die-cast aluminum construction, with die-cast back mounting plate and extruded aluminum body.

**Gasket:** Black silicone gasket to seal out contaminants, standard.

**Fasteners:** Hidden fasteners allow for cover removal to facilitate installation and service.

**Reflector:** Precision formed semi-specular aluminum formed for maximum reflectance.

**Socket: PL:** Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact. **HID: Remote only:** G12 base porcelain socket. Both incandescent and HID have double silicone jacket wire with a 200°C rating.

**Ballast: PL:** Fluorescent high power factor electronic, U.L. listed ballast standard. **HID:** Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a 5 year warranty.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

**Mounting:** Mounts directly to standard outlet box. 18" long pendant standard.

**Options: PL:** Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only.

