

FCCSeries

9" Die cast aluminum
up/down light cylinder



Cylinder

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Source/Wattage	Ballast	Finish	Accessories	
FCC920 Vertical	120V 277V 347V (Canada)	13Q 90W Par38 18Q 250 Par38 26T 150W A21 32T	39MH G12 70MH G12 50MH 70MH	E Electronic M Magnetic	BK Black WH White CC Custom color	D Dimming (consult factory) EC E-coat EMR Emergency back up (PL only) F Fuse Q Quartz restrike (▶ HID ballast only)

▶ not available with 277V or 347V electronic ballast

Product Information

Listings: U.L. listed for wet locations.

Housing: Marine grade corrosion resistant heavy wall high pressure die-cast aluminum construction, with die-cast back mounting plate.

Baffle: Bottom - die cast aluminum baffle in fixture color unless otherwise specified.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Diffuser: Lens is heat resistant, clear tempered glass.

Reflector: Heavy gauge spun reflector with clear specular Alzak® finish cone.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **HID:** Medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating.

Integral Ballast: PL: Fluorescent high power factor electronic, U.L. listed ballast standard. **HID:** Dual voltage (120/277) core and coil, high power factor, thermally protected ballast, standard.

Mounting: Mounts directly to standard recessed junction box.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Options: PL: Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only.

