

FCC Series

Large diameter die cast aluminum mono up/down light cylinder



Catalog Number

Series	Voltage	Wattage	Ballast	Finish	Accessories
FCCM813 up / down wall	120V 277V 347V (Canada)	100W T4 39MH G12 150W T4 70MH G12	E Electronic	BK Black WH White CC Custom color	D Dimming (PL only) EC E-coat EMR Emergency back-up, remote (PL only) F Fuse

Product Information

Listing: U.L. listed for wet locations.

Housing: Marine grade corrosion resistant heavy wall high pressure die-cast aluminum construction, with die-cast back mounting plate and extruded aluminum body. For HID unit die cast ballast box is included.

Gasket: Black silicone gasket to seal out contaminants, standard.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Top lens is 3/8" thick, beveled tempered clear heat resistant standard.

Reflector: Precision formed semi-specular aluminum formed for maximum reflectance.

Socket: INC (120V only): Mini cand socket. **HID:** G12 base. Nickel plated shell, spring loaded contact. Both incandescent and HID sockets have double silicone jacket wire with a 200°C rating.

Ballast: HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a 5 year warranty.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Mounts directly to standard outlet box.

Options: PL: Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only.

