



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

FCCSQ Series

6" Diameter die cast aluminum square up/down light cylinder



Catalog Number

| Series | Voltage | Wattage | Ballast | Finish | Accessories |
|-----------------------|----------------------------------|-------------------------------|-------------------------------------|---|---|
| FCCSQ618 up/down wall | 120V 277V 347V (Canada) | 13Q 75W Par 30 18T ▷26T | ▷39MH Par20 20MH G12 39MH G12 | E Electronic BK Black WH White CC Custom color | D Dimming (consult factory) EC E-coat EMR Emergency back-up, remote (PL only) F Fuse |

Product Information

Listing: U.L. listed for wet locations.

Housing: Marine grade corrosion resistant heavy wall high pressure die-cast aluminum construction, with die-cast back mounting plate and extruded aluminum body. For HID unit die cast ballast box is included.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Top lens is 3/8" thick, beveled tempered clear heat resistant standard.

Reflector: Precision formed semi-specular aluminum formed for maximum reflectance.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only)/ Par HID:** Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating. **HID:** G12 base for 39 MH, and G8.5E base for 20MH.

Ballast: PL: Fluorescent high power factor electronic, U.L. listed ballast standard. **HID:** Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a 5 year warranty.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Mounts directly to standard outlet box.

Options: PL: Fuses, dimming ballasts and emergency battery packs are also available. Battery packs are remote mount only.

