




FCCSQ Series

8" Die cast aluminum
down light surface
mount square
cylinder



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCCSQ809	120V -277V	PL: 26T, 32T, 42T	BL Black	347V Voltage
FCCSQ817		HID: 39MH G12, 70MHG12 150MH G12 (FCCSQ817 DPD only)	BZ Bronze	DPD Distribution pattern down
			CC Custom Color	DPUD Distribution pattern up/down
			SL Silver	EC E-coat (use for coastal/ severe wheather areas)
			WH White	F Fuse

Product Information

Listing: UL & cUL listed for wet locations. IP65 rating.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum and extruded aluminum construction.

Gasket: Extruded silicone to provide maximum protection against contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, clear, tempered glass.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. HID: G12 base porcelain socket and double silicone jacket wire with a 200°C rating.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.


Finish

Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat as standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting

Mounts directly to standard outlet box.

FCCSQ809



FCCSQ817

