



FCCSQ Series

9" Die cast aluminum square cylinder



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Ballast	Finish	Accessories
FCCSQ920	120V - 277V	PL: 26T, 42T, 57T	E Electronic	BK Black	D Dimming (consult factory)
FCCSQ920P		HID: 70G12, 150G12	M Magnetic	BZ Bronze	EC E-coat (use for coastal /severe wheather areas)
FCCSQ920W		250MH		CC Custom Color	F Fuse
				WH White	EMR Emergency backup remote (PL only 12ft max)
					SB Sandblasted reflector
					347V Voltage

Product Information

Listing: UL & cUL listed for wet locations. IP65 rating.

Housing: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum and extruded aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, UV stabilized, opal, polycarbonate diffuser.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. HID: Medium base pulse rated 4KV porcelain socket or G12 base. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating. Mogul base sockets for 250MH.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard for 150MH and less, magnetic ballast standard for 175MH and greater. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat is standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Pendant: Pendant mount is 18" standard.

Mounting: Mounts directly to standard outlet box.

