



FCW Series

Die cast aluminum
linear post



corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Source/Wattage	Finish	Accessories
FCW5024	120V - 277V	PL: 26W, 32W, 42W HID: 70MH	BK Black BZ Bronze CC Custom Color SL Silver WH White	347V Voltage EC E-coat (use for coastal /severe weather areas) F Fuse

Product Information

Listing: UL & cUL listed for wet locations. IP65 rating.

Construction: Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction.

Gasket: Neoprene continuous closed cell gasket to seal out contaminants.

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Impact resistant, UV stabilized, clear, polycarbonate diffuser.

Reflector: Precision formed semi-specular aluminum for maximum reflectance.

Socket: PL: Two pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. HID: G12 or medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200° C rating.

Ballast: PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder coat is standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting: Mounts directly to standard outlet box.

