




## FCD1217, FCD1722

Cool touch exterior 316 stainless steel face below-grade mounted fixture



Corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

### Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCD1217 FCD1722	120V - 277V	39MH G12 70MH G12 150MH G12 (FCD1722 only)	SS Stainless steel	347V Voltage DPA Distribution pattern asymmetrical DPN Distribution pattern narrow DPW Distribution pattern wide

### Product Information

**Listing:** UL and cUL listed for wet locations.

**Construction:** Marine grade, corrosion resistant, heavy walled, high pressure die cast aluminum construction with 316 machined stainless steel trim (PVC sleeve included).

**Gasket:** Neoprene continuous closed cell urethane 'O' ring gasket to seal out contaminants.

**Fasteners:** Captive and recessed stainless steel, tamper resistant hex socket screws.

**Diffuser:** Lens is heat resistant, clear, tempered glass. \*Includes captive air within double closure glass to ensure surface temperature less than 70°C.

**Reflector:** Etched aluminum reflector for smooth distribution.

**Socket:** HID: G12 base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating.

**Ballast:** HID: Integral dual voltage (120V/277V) electronic, high power factor, thermally protected ballast. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

**Finish:** Stainless steel brushed finish.

**Mounting:** Concrete pour.

