

FCSL Series

Exterior die cast
midsize step light with
die cast faceplate for
masonry applications



Step light

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Ballast	LED diode	Finish	Accessories
FCSL201 Open face	120V	2/5BX ◀ 120V only 39MH ▽	E Electronic	WH White	BK Black	DWR Dry wall wings for remodeling applications
FCSL203 Louvered face	277V	2/7BX ◀ 25W T10 50MH ▽	M Magnetic	Consult factory for amber, blue, green or red	WH White CC Custom color	EC E-coat EMR Emergency back-up, remote (not available LED)
		2/9BX ◀ 50WQ T4				F Fuse
		2/13BX ◀ 35HPS ▽				LRI Long range igniter
		13Q ◀ 50HPS ▽				P Prismatic lens, C73
		▷26Q ◀				PCL Polycarbonate lens (PL only)
						RSDT Step down transformer remote (use with INC 277V)
						SLH Horizontal spread lens
						SLV Vertical spread lens

LED - New!

4-1 watt diodes (total 4 watt)
4-3 watt diodes (total 12 watt)

- ▷ Recommended lamping
- ◀ Electronic only
- ▽ Remote ballast only (may require long range igniter)
- ◀ All 2 lamp units are 120V magnetic only.

Product Information

Listing: U.L. listed for interior and exterior wet locations.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction, with (2) 7/8" knockouts.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is 1/8" thick, tempered opal glass, clear for 203, heat resistant, standard.

Reflector: Precision formed, specular clear for maximum reflectance.

Socket: PL: Two pin or four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment.

INC (120V only): Mini-can base for incandescent quartz, or medium base, porcelain. **HID:** Medium base, 4KV pulse rated, porcelain socket. Nickel-plated shell, spring loaded contact and double silicone jacket with 200°C rated leads.

LED: 1 watt or 3 watt LumiLed Luxeon warm white diodes with a precision 18° beam angle lens and tilted at a 45° angle to project through the die cast louver to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 277V. Consult factory for color changing or multi-color combinations.

Ballast: PL: Fluorescent normal power factor core and coil, U.L. listed ballast standard. **HID:** Dual voltage (120/277) core and coil, high power factor, thermally protected ballast standard, remote.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Concrete pour. Consult factory on accessories for drywall application.

