




New!



FC SL Series

Exterior die cast large step light with die cast faceplate for masonry applications

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Ballast	LED Diode	Finish	Accessories
FC SL251 open face	120V 277V	▷ 1/27BX ◁ 120V only 2/40W T10 2/50W T4	E Electronic	WH White Consult factory for amber, blue, green or red	BK Black WH White CC Custom color	DWR Dry wall wings for remodeling applications EC E-coat EMR Emergency back-up, remote (PL only) F Fuse P Prismatic lens, C73 PCL Polycarbonate lens (PL only) RSDT Step down transformer remote (use with INC 277V) SLH Horizontal spread lens SLV Vertical spread lens
	LED	6-1 watt diodes (total 6 watts) 6-3 watt diodes (total 18 watts)				

▷ Recommended lamping

◁ Electronic only

Product Information

Listing: U.L. listed for interior and exterior wet locations.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction. Two 7/8" KO for through wiring.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is 1/8" thick, tempered opal glass, heat resistant, standard.

Reflector: Precision formed specular clear for maximum reflectance.

Socket: PL: Four pin (electronic) plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Mini-can base for incandescent quartz, or medium base, porcelain. **HID:** G8.5 bi-pin porcelain socket. Nickel-plated shell, spring loaded contact and double silicone jacket with 200°C rated leads.

LED: 1 watt or 3 watt LumiLed Luxeon warm white diodes with a precision 18° beam angle lens, projected through the lens to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 277V. Consult factory for color changing or multi-color combinations.

Ballast: PL: Fluorescent high power factor electronic, U.L. listed ballast standard. **HID:** Electronic ballast standard. Ballast is thermally protected and is rated HPF > 90% THD < 10%.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Concrete pour. Consult factory on accessories for drywall application.

