


FCSL Series

Exterior die cast large step light with die cast faceplate for masonry applications



Step light

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Ballast	LED diode	Finish	Accessories	
FCSL301 Open face	120V	2/26Q< 120V only	2-39MH△	E Electronic	WH White	BK Black	DWR Dry wall wings for remodeling applications
FCSL303 Louvered face	277V	27BX< 2/40W T10	1/2-35HPS△	M Magnetic	WH White	WH White	EC E-coat
		36BX< 2/50WQ T4	1/2-50HPS△		CC Custom color	CC Custom color	EMR Emergency back-up, remote
		▷39BX<					F Fuse
		120V only magnetic					LRI Long range igniter
		2/9BX					P Prismatic lens, C73
		2/13BX					PCL Polycarbonate lens (PL only)
		LED New!					RSDT Step down transformer remote (use with INC 277V)
		8-1 watt diodes (total 8 watts)					SLH Horizontal spread lens
		8-3watt diodes (total 24 watts)					SLV Vertical spread lens
		Note: SLH or SLV optional lens are recommended					

▷Recommended lamping

<Electronic only

▽Remote ballast only (may require long range igniter)

Product Information

Listing: U.L. listed for interior and exterior wet locations.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction. Two 7/8" KO for through wiring.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is 1/8" thick, tempered opal glass, heat resistant, standard.

Reflector: Precision formed, specular clear for maximum reflectance.

Socket: PL: Two pin (magnetic) or four pin (electronic) plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Mini-can base for incandescent quartz, or medium base, porcelain. **HID:** Medium base, 4KV pulse rated porcelain socket. Nickel-plated shell, spring loaded contact and double silicone jacket with 200°C rated leads.

LED: 1 watt or 3 watt LumiLed Luxeon warm white diodes with a precision 18° beam angle lens and tilted at a 45° angle to project through the die cast louver to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 277V. Consult factory for color changing or multi-color combinations.

Ballast: PL: Fluorescent normal power factor core and coil, U.L. listed ballast standard. **HID:** Dual voltage (120/277) core and coil, high power factor, thermally protected ballast standard, remote.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Concrete pour. Consult factory on accessories for drywall application.

