


FCSL Series

Exterior die cast round eye lid step light for masonry applications



Step light

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Ballast	LED diode	Finish	Accessories
FCSL400	120V 277V	5BX 7BX ▷13T	M Magnetic E Electronic (13T only)	WH White Consult factory for amber, blue, green or red	BK Black WH White CC Custom color	DWR Dry wall wings for remodeling applications EC E-coat EMR Emergency back-up, remote (PL only) F Fuse P Prismatic lens PCL Polycarbonate lens (PL only) SLH Horizontal spread lens SLV Vertical spread lens

LED^{New!}
3-1 watt diodes (total 3 watt)
3-3 watt diodes (total 9 watt)

▷Recommended lamping

Product Information

Listing: U.L. listed for interior and exterior wet locations.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction, with (2) 7/8" knockouts.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is 1/8" thick, tempered sandblasted glass, heat resistant, standard.

Reflector: Precision formed reflector for maximum reflectance.

Socket: PL: Two pin plug-in type compact fluorescent lamp holder or four pin for electronic ballast (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Mini-can base for incandescent quartz.

LED: 1 watt or 3 watt LumiLed Luxeon warm white diodes with a precision 18° beam angle lens and tilted at a 45° angle to project through the die cast louver to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 240V. Consult factory 277V, color changing or multi-color combinations.

Ballast: PL: Fluorescent normal power factor core and coil, U.L. listed ballast standard.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Concrete pour. Consult factory on accessories for drywall application.

