

FCSL Series

Exterior die cast round step light with die cast face plates for masonry applications



Step light

Catalog Number

Series	Voltage	Wattage	Ballast	Diode color	Finish	Accessories
FCSL401 Open face	120V	5BX 50WQ T4	M Magnetic	WH White	BK Black	DWR Dry wall wings for remodeling applications
FCSL402 Louvered face	277V	7BX ▷13T	E Electronic (13T only)	Consult factory for amber, blue, green or red	WH White CC Custom color	EC E-coat EMR Emergency back-up, remote (PL only) F Fuse P Prismatic lens PCL Polycarbonate lens (PL only) SL Spread lens

LED^{New!}
4-1 watt diodes (total 4 watts)
4-3watt diodes (12 total watts)

▷Recommended lamping

Product Information

Listing: U.L. listed for interior and exterior wet locations.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction. Two 7/8" KO for through wiring.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is 1/8" thick, tempered opal, clear for 402 glass, heat resistant, standard.

Reflector: Precision formed aluminum for maximum reflectance.


Socket: PL: Two pin plug-in type compact fluorescent lamp holder or four pin for electronic ballast (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Mini-can base for incandescent quartz.

LED: 1 watt or 3 watt LumiLed Luxeon warm white diodes with a precision 18° beam angle lens and tilted at a 45° angle to project through the die cast louver to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 277V. Consult factory for color changing or multi-color combinations.


Ballast: PL: Fluorescent normal power factor core and coil, U.L. listed ballast standard. Electronic available 13T only.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Concrete pour. Consult factory on accessories for drywall application.



FC SL401
Open Die Cast Face



FC SL402
Louvered Die Cast Face

