





FCSL Series

Square recessed LED
with die cast faceplate



FCSL651



FCSL655

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCSL651	120V - 240V	LED - 5W	BK Black	EC E-Coat (use for coastal/severe weather areas)
FCSL655		LED - 2W	BZ Bronze CC Custom color SL Silver WH White	PVC PVC Sleeve

Product Information

Listing: U.L. & cUL listed for interior and exterior wet locations.

Housing: Marine grade corrosion resistant heavy wall high pressure die-cast aluminum construction housing and faceplate, with die-cast back mounting plate.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Lens is heat resistant, white tempered glass.

LED: 2 watt or 5 watt white diodes with a precision 18° beam angle lens, projected through the lens to maximize the light output and performance. Integral inverter and driver potted with a variable input of voltage from 120V to 240V. Consult factory for color changing or multi-color combinations and other voltage options.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate. E-coat comes with a 5 year warranty.

Mounting: Concrete pour.

