




corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

## FCW Series

Exterior die-cast aluminum architectural wall or pier mount

New!



Front view

### Catalog Number

Series	Voltage	Source/Wattage	Ballast	Finish	Accessories
FCW1080	120V 277V 347V (Canada)	13Q 60 A19 ▷26T	Remote ballast only 39MH 50MH  35HPS 50HPS	E Electronic M Magnetic BK Black WH White CC Custom color	EC E-coat EMR Emergency back-up, remote (indoor PL only) F Fuse LRI Long range igniter O Opal lens

### Product Information

**Listing:** U.L. listed for wet locations.

**Housing & top:** Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction.

**Gasket:** Extruded silicone to provide maximum protection and to seal out contaminants.

**Fasteners:** Captive stainless steel, tamper resistant, hex socket screws.

**Diffuser:** Impact resistant UV stabilized clear polycarbonate diffuser tube.

**Socket: PL:** Four pin plug-in type compact fluorescent lamp holder, assures precise optical alignment. (Lamps by others)

**INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact. **HID:** Medium base 4KV pulse rated porcelain socket. Nickel plated shell, spring loaded contact. Incandescent and HID socket wire is double silicone jacket wire with a 200°C rating.

**Ballast: PL:** Fluorescent high power factor electronic, U.L. listed ballast standard. **HID Remote:** Dual voltage (120/277V) high power factor, thermally protected ballast standard, remote.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate.

**Mounting:** Mounts directly to standard outlet box. Additional mounting holes allow unit to be attached directly to mounting surface.

FCW1080

