



Type:	Approved:
Fixture:	
Project:	

FCW Series

Interior / Exterior architectural triangular wall sconce



Catalog Number

Series	Voltage	Source/ Wattage	Ballast	Finish	Accessories		
FCW1040	120V	13Q	100INC	50MH	E Electronic	BK Black	D Dimming
	277V	26T	200INC	70MH	M Magnetic	WH White	EC E-Coat
	347V (Canada)	32T		▷100MH		CC Custom Color	EMR Emergency Backup, Remote (PL only)
		▷42T		35HPS		BZ Bronze	F Fuse
				50HPS		SL Silver	PCL Polycarbonate Lens (PL only)
				70HPS			PE Photo Eye
				100HPS			QR Quartz Restrike (▷HID Only)
							SB Sandblasted Lens

▷Recommended lamping
▶Not available with 277V or 347V

Product Information

Listing	UL listed for wet location in down position only, damp listing for up position.
Housing	Corrosion resistant, heavy gauge CRS. Die formed and seam welded for solid construction.
Gasket	Neoprene continuous closed cell gasket to seal out contaminants.
Fasteners	Captive stainless steel, tamper resistant, hex socket screws.
Diffuser	Lens is 1/8" thick, tempered clear, heat resistant.
Socket	PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. INC (120V only): Medium base porcelain socket. Nickel plated shell, spring loaded contact. HID: Medium base 4KV pulse rated porcelain socket. Nickel plated shell, spring loaded contact. Incandescent and HID socket wire is double silicone jacket wire with a 200°C rating.
Ballast	PL: Fluorescent high power factor electronic ballast, standard UL listed ballast. HID: Standard dual voltage (120/277V) core and coil, high power factor ballast.
Finish	Seven stage preparation process that includes TGIC super polyester powder-coat is standard. Optional E-Coat process added to standard finish including zinc phosphate.
Mounting	Mounts directly to standard outlet box. Additional mounting holes allow unit to be attached directly to mounting surface.

Product Dimensions

