

## FCWS Series

Wrap two lamp  
up/down wall  
sconce



Wall sconce

Shown with special order finish.

corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

## Catalog Number

Series#	Voltage	Wattage	Ballast	Finish	Accessories	
FCWS6350	120V	2-▷13BX◁	1/2-60W T10	E Electronic	BK Black	BS Bi-level switching
	277V	2-13Q		M Magnetic	WH White	CG Clear glass
	347V	2-18Q			RB Ribbed Metal (as shown)	D Dimming (Consult factory)
	(Canada)	2-▷26Q			SA Satin aluminum	EC E-coat
				CC Custom color (solid face only)	EMR Emergency back-up, remote (PL only)	
					F Fuse	
					LC Laser cut design	
					PCH Pull chain	

▷Recommended lamping

◁magnetic ballasts only

## Product Information

**Listings:** U.L. listed. Meets ADA requirements.

**Housing:** Roll formed heavy gauge aluminum is standard. Backplate and ballast housing are formed heavy gauge cold rolled steel with reflective finish.

**Diffusers:** **PL:** Laser cut .187 white opal acrylic is standard. Sandblasted or colored acrylic are available. Specify when ordering. **INC:** Tempered glass.

**Socket:** **PL:** Two pin plug-in type compact fluorescent lamp holder, assures precise optical alignment. Electronic and dimming versions require four pin socket and lamp. (Lamps by others)

**INC (120V only):** Medium base, T10, porcelain.

**Ballast:** **PL:** Integral electronic fluorescent high power factor, UL listed ballast, standard.

**Finish:** Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate

**Mounting:** To standard electrical box, in masonry, use 4 x .250" x .750" screws with lead anchors. (Box and fasteners by others.)

