

FCWS Series

Die cast aluminum
wall / ceiling mount
interior / exterior



Wall sconce

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	#/Lamps	Wattage	Ballast	Finish	Accessories	
FCWS8051	120V	1	13BX	2/25W T10	E Electronic	BK Black WH White CC Custom color	CUSG Custom graphic (Consult factory) D Dimming (consult factory) EC E-coat F Fuse EMR Emergency back-up, remote (PL only) LCP Laser cut face plate (Consult factory)
	277V	2	18Q				
	347V		▷26Q				
	(Canada)		1/20W T-5 Circline				
			1/22W T-9 Circline				
		1/30W T-9 Circline					
		1/28W 2-D					
		1/38W 2-D					

Product Information

Listings: U.L. listed for interior and exterior wet locations. Meets ADA requirements.

Housing & Faceplate: Marine grade corrosion resistant heavy walled high pressure die-cast aluminum construction. With cooling fins to maximize component life.

Gasket: Neoprene continuous closed cell 'O' ring gasket to seal out contaminants.

Fasteners: Captive and recessed stainless steel, tamper resistant, hex socket screws.

Diffuser: Impact resistant UV stabilized opal polycarbonate.

Reflector: Precision formed semi-specular aluminum formed for maximum reflectance.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. **INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating.

Ballast: PL: Fluorescent high power factor electronic, U.L. listed ballast standard.

Finish: Five stage preparation process that includes chromate conversion and TGIC super polyester powder-coat as standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Mounting holes allow unit to be attached directly to mounting surface.

