



## FCWS8200

Die cast vertical or horizontal mounted disk wall sconce



corporate  
t 800 900 1730  
f 630 889 8106  
3609 Swenson Ave  
St. Charles, IL 60174

### Catalog Number

Series	Voltage	Wattage	Finish	Accessories
FCWS8200	120V - 277V	PL: 26T, 32T INC: 75W PAR30 HID: 39MH PAR30, 39MH G12 LED: 20W	SS Stainless Steel	CF Color filter EC E-coat (use for coastal/severe weather areas) F Fuse 347V Voltage
FCWS8201				

### Product Information

**Listing:** UL & cUL listed.

**Construction:** Marine grade, corrosion resistant, heavy walled aluminum construction.

**Fasteners:** Captive and recessed stainless steel, tamper resistant hex socket screws.

**Diffuser:** Lens is 1/8" thick, tempered, clear, heat resistant.

**Socket:** PL: Four pin plug-in type compact fluorescent lamp holder (lamp by others). Holder assures precise optical alignment. Electronic and dimming versions require four pin socket and lamp. INC: Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating. HID: Medium base or G12 base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating.


**LED:** Integral inverter and driver potted with a variable input of voltage from 120V to 240V. Consult factory for color changing or multi-color combinations and other voltage options.

**Ballast:** PL: Fluorescent high power factor electronic, UL listed ballast standard. HID: Electronic ballast standard. Ballast is thermally protected and is rated HPF>90% THD<10%. Ballast has a manufacturer issued warranty up to 5 years. Electronic universal voltage 120V through 277V is standard. Please consult factory for other voltage options.

**Finish:** Stainless steel brushed finish.

**Mounting:** Mounts directly to standard outlet box.

FCWS8200



FCWS8201

