



FCWS Series

Quarter cylinder uplight wall sconce



Wall sconce

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	#/Lamps	Source/Wattage	Ballast	Finish	Accessories
FCWS8460	120V	1	13Q	E Electronic	BK Black	DR Remote dimming ballast (Consult factory) EC E-coat EMR Emergency back-up, remote F Fuse
	277V	2	18T		BA Brushed aluminum	
	347V (Canada)		26Q		WH White	
			1/18 BX		SA Satin aluminum	
			1/27 BX		CC Custom color	
		▷1/36 BX				
		1/39 BX				

▷Recommended lamping

Product Information

Listing: UL listed. Meets ADA requirements.

Housing: Corrosion resistant heavy gauge aluminum. .

Fasteners: Hidden fasteners allow for cover removal to facilitate installation and service.

Diffuser: Lens is 1/8" thick clear tempered glass standard.

Socket: Four pin plug-in type compact fluorescent lamp holder, assures precise optical alignment. Electronic and dimming versions require four pin socket and lamp. (Lamps by others)

Ballast: Integral ballast compartment with electronic, thermally protected ballast is rated for compact fluorescent lamp. (Lamp by others)

Finish: Five stage preparation process that includes ion phosphate and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: To standard electrical box, in masonry, use 4 x .250" x .750" screws with lead anchors. (Box and fasteners by others.)

