

FCWS Series

Arm mount wall sconce



Wall sconce

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

| Series | Voltage | # / Wattage | | | Ballast | Finish (Bowl/Arm) | | Accessories |
|----------|------------------|-----------------|-------|--------------------------------------|--------------|---------------------|---------------------|--|
| FCWS9001 | 120V | 2/13Q | 2/25W | 1/50MH | E Electronic | BA Brushed aluminum | BA Brushed aluminum | F Fuse |
| FCWS9002 | 277V | 2/18T | 2/40W | 1/70MH | M Magnetic | BK Black | BK Black | D Dimming |
| | 347V (Canada) | ▷2/26Q 1/57T | 2/60W | 1/100MH 1/70MH G12 1/150MH G12 | | WH White | WH White | (consult factory) |
| | | | | | | CC Custom color | CC Custom color | DC Acrylic dust cover (PL only) |
| | | | | | | | | EC E-coat |
| | | | | | | | | EMR Emergency back-up, remote (PL only) |
| | | | | | | | | Q Quartz restrike (▷HID integral ballast only) |
| | | | | | | | | WBB Wall mount ballast box |

▷Recommended lamping

▶not available with 277V or 347V electronic ballast

Product Information

Listing: UL listed .

Housing: Support arm is heavy gauge aluminum extrusion. Bowl is heavy gauge spun aluminum. Backplate and deep wall cover are heavy gauge formed steel.

Socket: PL: Two pin plug-in type compact fluorescent lamp holder, assures precise optical alignment. Electronic and dimming versions require four pin socket and lamp. (Lamps by others) **INC (120V only):** Medium base porcelain socket. Nickel plated shell, spring loaded contact and double silicone jacket wire with a 200°C rating. **HID:** Medium base, 4KV pulse rated, porcelain socket. G12 base porcelain socket.

Ballast: PL: Fluorescent high power factor electronic ballast, UL listed ballast standard. **Remote HID:** Remote mount is standard. Dual voltage (120/277V) encased and potted, high power factor, thermally protected ballast standard. Core and coil ballast, available. Consult factory for wall mount ballast box applications.

Finish: Five stage preparation process that includes ion phosphate and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: Supplied with support arm and canopy set for mounting directly to standard outlet box. Back mounted for wall installation supported by (4) 1/4-20 bolts.

