

FCWS Series

Deco wall sconce



Wall sconce

corporate
t 800 900 1730
f 630 889 8106
3609 Swenson Ave
St. Charles, IL 60174

Catalog Number

Series	Voltage	#/Lamps	Wattage per Bowl			Ballast	Finish (Bowl/Arm)		Accessories
FCWS9003	120V	1	26Q	60W T10	1/70MH	E Electronic	BK Black	BK Black	D Dimming
	277V	2	32T	100W	1/100MH	M Magnetic	WH White	WH White	(PL only) (consult factory)
	347V		36 BX	150W	1/150MH		CC Custom color	CC Custom color	DC Dust cover-polycarbonate lens (PL only)
	(Canada)		39 BX	1/250Q	1/175MH				EC E-coat (painted finish)
			42T						EMR Emergency back-up, (PL only)
			▷57T					F Fuse	

▷Recommended lamping
HID ballasts remote mount

Product Information

Listings: U.L. listed.

Bowls / Armature: Bowl is spun aluminum. Armature is drawn heavy wall aluminum.

Canopy: Rectangular aluminum deco canopy cover with reinforcement plate.

Socket: PL: Four pin plug-in type compact fluorescent lamp holder, assures precise optical alignment. Electronic and dimming versions require four pin socket and lamp. (Lamps by others)

INC (120V only): Medium base porcelain socket. Nickel plated shell, spring loaded contact. **HID:** Medium base pulse rated 4KV porcelain socket. Nickel plated shell, spring loaded contact.

Ballast: PL: Integral fluorescent UL listed ballast, standard, electronic only. **Remote HID:** Dual voltage (120/277) encased and potted, high power factor, thermally protected ballast, standard. Remote ballast tray standard supplies ballast assembled on tray for mounting.

Finish: Five stage preparation process that includes ion phosphate and TGIC super polyester powder-coat is standard. Optional E-coat process added to standard finish including zinc phosphate.

Mounting: To standard electrical box, in masonry, use 4 x 1/4-20 screws with anchors. (Box and fasteners by others.)

