



FCW3800 & 3801

Low Profile Exterior Decor





New Low Profile Design

Interior/Exterior Luminaires



Protected against 20 joules impact



ADA Compliant

Americans with Disabilities Act



Dust & Jets of Water Protected



ETL Safety Standards Certified
Intertek

- Safe, Sealed & Reliable
- Long Service Life
- Ideal for Wet Environments
- IP66 Ingress Protection
- Vandal Resistant, IK10 Impact Rating
- 0-10V, 1% Dimming, optional ELV
- Clean Appearance, No Visible Fasteners
- Excellent for both Wall and Ceiling mounting
- Narrow two inch width
- Available AAMA 2605 finish
- Perfect for small, restrictive spaces
- 5-Year Warranty
- Lifetime Vandal Resistance Warranty





- Ultra Low Profile Design
- Hidden Fasteners
- Ideal for Wall or Ceilings

CLEAN & CONTEMPORARY

These fixtures feature a low profile two inch width, perfect for wall or ceiling mounting in small, restrictive spaces. These durable, long-lasting luminaires accentuate the most demanding atmospheres, featuring no visible fasteners for a clean, contemporary appearance. All products provide a 5-Year limited warranty and a Lifetime Vandal Resistance Warranty.





Apartments



Hospitals

Durable, Quality Lighting for Interior and Exterior Decor Applications



Schools



Hotels



Walkways



Stairs

Water and Impact Resistant Assures Long Lasting Value



Safe for Wet Applications

IP66 Ingress protection



Impact Resistant Design

IK10 Impact rating



Weather Resistant Super TGIC polyester powder coat finish, 5000hr salt spray test (ASTM B117) compliant with Florida/AAMA 2604 specification with an optional AAMA 2605.



Investment protection with long service life, 5-Year Limited Warranty, Lifetime Vandal Resistance Warranty.



Vandal resistant construction with high impact, UV stabilized polycarbonate diffuser. Marine grade die cast aluminum housing and lens trim. IK10 Impact rating.



IP66 Ingress protection assure protection from dirt, insects and moisture penetration.



Clean, Modern Appearance

Thin Profile & Hidden Fasteners


13" Low Profile Round and Square Designs



FCW3800

ADA


UNIV, 347V
3000K, 4000K
1414-2619 lm nominal



FCW3801

ADA

UNIV, 347V
3000K, 4000K
1486-2772 lm nominal







FCW3800-BRO
DH-12221