

DIRECTIONAL WALL CYLINDER - INSTALLATION INSTRUCTIONS

CAUTION: BEFORE CONNECTING THE FIXTURE TO A POWER SUPPLY, MAKE SURE THE POWER IS SWITCHED OFF.



OUTDOOR LIGHTING

t 800.900.1730 f 630.889.8106
3609 Swenson Ave. St. Charles, IL 60174

Including FCWSQ606



DETAILED ILLUSTRATION

GENERAL:

1. Fixture must be installed by licensed electrician.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.
3. Before starting the installation, make sure all electricity has been turned off and electrical breaker has been locked out and tagged out.
4. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur.

INSTALLATION INSTRUCTIONS:

NOTE: This fixture must be mounted horizontally with the removable access lens panel to be mounted in the down position.

- 1) Wire power supply wires to fixture wires, be certain to make secure connections.
- 2) Install mounting cleat to 4" octagonal junction box.
- 3) Mount fixture to wall mounting cleat horizontally with removable access lens panel to be mounted in the down position, add two nuts to secure fixture to plate.
- 4) Use a bead of silicone caulk around the edge of the mounting arm where it meets the mounting surface to create waterproof seal between the fixture and the wall.
- 5) Restore power to circuit then test fixture.

NOTE: LED lamping is integral and NOT intended for general servicing.

IMPORTANT: All FC|SSL products can be cleaned with non-abrasive and chemical free agents. Use a soft cloth with mild detergent on exterior only.

