

FCB460 FCB460A







Date:	Approved
Туре:	
Fixture:	

Project:

FCB460 Exterior 316 stainless steel and die-cast aluminum bollard. Round 8" diameter and 43" tall, louvered bollard with optional house shield for 180° or 270° cut off. Designed and built to provide downward directed light completely surrounding the luminaire, or optionally, internally shielded to 180° or 90° light pattern. FCB460A is Certified by the Florida Fish & Wildlife Conservation Commission as approved for Wildlife Lighting in areas with protected environments.

SPECIFICATIONS

PHYSICAL	
dimensions	43"H x 8"D
weight	25 lbs
housing	marine grade 316 stainless steel housing
lens	clear, heat resistant, tempered glass globe
mounting	heavy wall base bracketing for bollard installation provides a unique mounting solution, so the tower body anchors flush to the ground without the appearance of a base plate, anchor bolts included
ingress protection	IP66: dry, damp, or wet locations
finish	marine grade 316 stainless steel housing

PERFORMANCE					
color temperature	CB460 - 2700K, 3000K, 3500K, 4000K				
lumen output	FCB460 - 932 lm, FCB460A - 147 lm				
lumen maintenance	L70 >70,000 hours				
color consistency	3 SDCM / 85 CRI				
operating temperature	-13°F to 122°F (-25°C to 50°C)				
warranty	5-Year limited warranty				

ELECTRICAL				
input voltage	Universal 120 - 277 VAC, optional: 347 VAC, 480 VAC			
power supply	Integral Class II, electronic high-power factor > 94% @ 120V			
certification	ETL/cETL Listed			
standards	UL1598/CSA C22.2 No. 250.0; UI 8750/CSA C22.2 No. 250.13/IES LM-79/LM-80			
power consumption	120 - 277 VAC @ 42W			
dimming	standard: 0-10V (10%), optional: ELV (120 VAC only) / DMX / DALI			



FCB460A Wildlife Lighting Certified by the Florida Fish & Wildlife Conservation Commission

Due to continuous development and improvements, specifications are subject to change without notice. Product use certifies agreement to FC Lighting terms and conditions.

US Commercial Lighting Manufacturer Since 1982

Specification Sheet

FCB460 FCB460A



Ordering Information

PART NUMBER

FCB460								
SERIES		VOLTAGE	HEIGHT	COLOR	LUMENS	FINISH		OPTIONS
FCB460	UNV	120 - 277 VAC	43 43"	827 (85CRI) 2700K	10L 932 lm (42W)	SS Stainless Steel	LD	0-10V Dimming
	120V	120 VAC (Photo Eye)		830 (85CRI) 3000K			ELV	ELV Dimming (120 VAC Only) (No PE Option)
	277V	277 VAC (Photo Eye)		835 (85CRI) 3500K	HS - 180° House Shield		SP20	20kV Surge Protector
	347V	347 VAC		840 (85CRI) 4000K	05L 463 lm (22W)		BBU	Battery Backup (Integral)
	480V	480 VAC					SP20-BBU	(2) 20kV Surge Protectors (1/LED Driver, 1/
					HS2 - 90° House Shield			BBU) and Battery Backup (Integral)
					03L 233 lm (12W)		PE120	Photo Eye for 120 VAC
							PE277	Photo Eye for 277 VAC
							HS	180° House Shield
							HS2	270° House Shield
							LAB ¹	Less Anchor Bolt Kit - for shipment separate of Anchor Bolt Kit

FCB460A				АМ	01L			
SERIES		VOLTAGE	HEIGHT	COLOR	LUMENS	FINISH		OPTIONS
FCB460A	UNV	120 - 277 VAC	43 43"	AM Amber (590-600nm)	01L 147 lm (30W)	SS Stainless Steel	LD	0-10V Dimming
	120V	120 VAC (Photo Eye)					ELV	ELV Dimming (120 VAC Only) (No PE Option)
	277V	277 VAC (Photo Eye)			HS - 180° House Shield		SP20	20kV Surge Protector
	347V	347 VAC			05L 73 lm (15W)		BBU	Battery Backup (Integral)
	480V	480 VAC					SP20-BBU	,
					HS2 - 90° House Shield			BBU) and Battery Backup (Integral)
					03L 36 lm (10W)		PE120	Photo Eye for 120 VAC
							PE277	Photo Eye for 277 VAC
							HS	180° House Shield
							HS2	270° House Shield
							LAB ¹	Less Anchor Bolt Kit - for shipment separate of Anchor Bolt Kit

ANCHOR BOLT KITS

A00450-01

Anchor Bolt Kit - Complete Anchor Bolt Kit shipped in advance of fixture.

¹ **Note**: Fixture must be mounted into FC Lighting supplied Anchor Bolt Kit shipped with or separate of fixture.

Consult Factory for other options and configurations.

To ensure you receive proper configurations for your lighting specifications, contact us directly about any unique application requirements. This may include but not be limited to lumen output, mounting needs, or electrical requirements.

Due to continuous development and improvements, specifications are subject to change without notice. Product use certifies agreement to FC Lighting terms and conditions.




US Commercial Lighting Manufacturer Since 1982

Specification Sheet

Physical




PRODUCT DIMENSIONS - STANDARD PRODUCT






Mounting Plate Diameter Ø 8" **Anchor Bolt Template** A00450-01 **Assembly**

(Includes the below items listed)





#	(A00450-01) (Includes below items)	
1	3/8" x 12" x 1" L Hook Anchor Bolt (94523B-4)	4
2	3/8" Flat Washer H-D Galv Steel	8
3	Anchor Bolt Wood Template	
4	Anchor Bolt Label	1
5	3/8" Hex Nut H-D Galv Steel 8	
6	Plastic Bag, Sealed	1


Due to continuous development and improvements, specifications are subject to change without notice. Product use certifies agreement to FC Lighting terms and conditions.





Photometry

OPTICAL DISTRIBUTION



IES MULTIPLIER					
Color Multiplier					
927	0.89				
930	0.96				
935	0.97				
940	1.00				

Lumen Output	932 lm @ 4000K		
Power Consumption	42 W		


OPTIONS


FIND IES FILES ON FCLIGHTING.COM

HS - 180° House Shield

HS2 - 270° House Shield

NOTE: House Shields are internal to the fixture.







Due to continuous development and improvements, specifications are subject to change without notice. Product use certifies agreement to FC Lighting terms and conditions.



Photometry

OPTICAL DISTRIBUTION






OPTIONS


FIND IES FILES ON FCLIGHTING.COM

HS - 180° House Shield

HS2 - 270° House Shield

NOTE: House Shields are internal to the fixture.





Due to continuous development and improvements, specifications are subject to change without notice. Product use certifies agreement to FC Lighting terms and conditions.