


FCSL2010



FCSL2010 13" exterior mid-size step light with 316 stainless steel louvered faceplate, for masonry or drywall construction. IP68 rated for damp, dry or wet locations.



SPECIFICATIONS

PHYSICAL

lengths/dimensions	13" W x 4.5" H x 3.9" D
weight	5 lbs
housing	Marine grade, corrosion resistant, heavy walled, high pressure die-cast housing with grade 316 stainless steel faceplate construction including snap-in Screwless faceplate standard. Optional captive recessed stainless steel tamper resistant screws (TRS) (torx pin heads w/tool provided). Back Box is high strength black plastic, F1 UV resistant, UL945VA rated.
lens	White glass lens
mounting	Concrete pour / masonry, solid composite / special construction, and drywall construction mounting kit included. Hanger bar mounting optional
ingress protection	Optical / driver unit is IP68 rated dry, damp or wet locations. All seals are injection molded silicone.
faceplate finish	Die cast aluminum faceplate. Six stage chemical iron phosphate conversion pre-treatment. Polyester powder coat finish, 18 µm Min., 5000hr salt spray test (ASTM B117) compliant with Florida / AAMA 2604 specification.


PERFORMANCE

color	2700K	3000K	3500K	4000K	5000K	Amber	Red	Blue
lifetime	> 70,000 hours / L70 or better							
color consistency	3 SDCM / 85 CRI (White)							
operating temperature	-13°F to 104°F (-30°C to 40°C)							
warranty	5-Year limited warranty (refer to website for details)							

ELECTRICAL

input voltage	Universal 120–277 Volt AC
power supply	Integral, electronic high-power factor > 94% @120V, THD of ≤ 20%
standards	cETLus
power consumption	7W (362 lm), 14W (651 lm)
dimming	standard: 0-10V dimming (10% minimum) optional: TRIAC dimming (120V only), 1% minimum 0-10V dimming

Due to continuous development and improvements, specifications are subject to change without notice. FC Lighting reserves the right to change lab test details or specifications without notice. Product use certifies agreement to FC terms and conditions.



Ordering Information

PART NUMBER

FCSL2010					SS		
MODEL	VOLTAGE	CCT	CRI	LUMENS	FINISH	OPTIONS	
FCSL2010	UNV	120V-277V	27K 2700K	CRI85 85 CRI	3L 362 lm (7W)	SS Stainless Steel	LD 0-10V Dimming - 1% minimum
	347V	347V (Remote only)	3K 3000K		6L 651 lm (14W)		ET TRIAC Dimming (120V only)
	120V	120V (for ET option)	35K 3500K				TRS Tamper Resistant Screws (Torx Pin)
			4K 4000K				HB Hanger Bar (Drywall Mounting)
			5K 5000K				LBB ¹ Less Back Box - for shipment separate of Back Box
STATIC COLORS							
FCSL2010	UNV	120V-277V	AMB Amber >560nm (14W)	N/A	N/A	SS Stainless Steel	ET TRIAC Dimming (120V only)
	347V	347V (Remote only)	RED Red (14W)	N/A	N/A		TRS Tamper Resistant Screws (Torx Pin)
	120V	120V (for ET option)	BLU Blue (14W)	N/A	N/A		HB Hanger Bar (Drywall Mounting)
							LBB ¹ Less Back Box - for shipment separate of Back Box
BACK BOX KITS							
A2000-BB-ETL	Back Box Kit - Complete Back Box shipped with mounting kit, shipped in advance of fixture.						
A2000-BB-ETL-HB	Back Box Kit w/ Hanger Bar - Includes (#A2000-BB-ETL) Complete Back Box shipped with mounting kit and Hanger Bar (HB), shipped in advance of fixture.						
¹ Note: Fixture must be mounted into FC Lighting supplied Back Box shipped with or separate of fixture.							


PRODUCT DIMENSIONS

width	13" W
height	4.5" H
depth	3.9" D


MOUNTING

back box width	12.6" W
back box height	4" H
back box depth	4" D


FCSL2010




Back Box Housing (Injection Molded Plastic)



Due to continuous development and improvements, specifications are subject to change without notice. FC Lighting reserves the right to change lab test details or specifications without notice. Product use certifies agreement to FC terms and conditions.




BACK BOX ASSEMBLIES & OPTIONS




Shims - (8 ea.) included w/ Fixture

Shims provided to compensate for Back Box misalignment.




Optional - Tamper Resistant Screws (TRS)


Torx screws w/ pin, finished to compliment faceplate finish.




Masonry Brackets - included w/ Back Box Kit




Drywall Brackets - included w/ Back Box Kit




Concrete Pour Setup - included w/ Back Box Kit



Optional - Hanger Bar (HB)




Due to continuous development and improvements, specifications are subject to change without notice. FC Lighting reserves the right to change lab test details or specifications without notice. Product use certifies agreement to FC terms and conditions.



Photometry

OPTICAL DISTRIBUTION

lumen output	362 lm	651 lm
power consumption	7W	14W



iti illuminations testing laboratory: Report #3706

Due to continuous development and improvements, specifications are subject to change without notice. FC Lighting reserves the right to change lab test details or specifications without notice. Product use certifies agreement to FC terms and conditions.

 US Commercial Lighting Manufacturer Since 1982

Specification Sheet

© FC Lighting, Inc. 3609 swenson ave • st. charles il • 60174 | fclighting.com | 800.900.1730

AG-DM-062623