

Industry's Largest
Trimless Offering

World Class
Durability

World Class
Easy Install



Features

Dimensions	1.77" x 2.48" 2.52" x 2.99" 3.15" x 3.23" 3.86" x 3.35"
Input Voltage	24VDC, Optional: UNV (120-277 VAC)
Power Consumption	1W - 9W
Color	2700K, 3000K, 3500K, 4000K 93 CRI (Standard)
Lumen Output	20 lm - 250 lm
Beam Spread	Direct View (120°)



Industry's Largest Trimless Offering

200,000+ Fixture
Combinations

One Family, Limitless
Solutions

World Class Durability Package

IP66, IP67, IP68,
IP69K

IK10 Max Impact
Resistance

2,200 lb Heavy Duty
Walkover

World Class Easy Install Package

Field Wirable IP68
Connection System

Toolless Lever-Lock
Termination Method

LUMEN DATA

ROUND

Model	Size	Wattage	Lumens
FCI-T175R	1.75" (45mm)	02W	50
		01W	20
FCI-T250R	2.50" (64mm)	05W	130
		03W	80
FCI-T300R	3.00" (80mm)	07W	180
		05W	140
FCI-T375R	3.75" (98mm)	09W	250
		07W	200

SQUARE

Model	Size	Wattage	Lumens
FCI-T175S	1.75" (45mm)	02W	50
		01W	20
FCI-T250S	2.50" (64mm)	05W	130
		03W	80
FCI-T300S	3.00" (80mm)	07W	180
		05W	140
FCI-T375S	3.75" (98mm)	09W	250
		07W	200

OPTICAL DISTRIBUTION

