OUTDOOR LIGHTING

Date:	**Approved:**
Type:	
Luminaire:	
Project:	

FCI-TXXXR(S)-WIN
(Window Series)

WORLD CLASS FEATURES

Asymmetrical Elliptical Window Grazing
- Seamless Sheet of Light Framing Windows

Flush Zero-Sightline Design

World Class Durability Package
- IP66, IP67, IP68, IP69K
- IK10 Max Impact Resistance
- 2,200 lb Heavy Duty Walkover

World Class Easy Install Package
- Field Wirable IP68 Connection System
- Toolless Lever-Lock Termination Method

SPECIFICATIONS

PHYSICAL

dimensions	**Luminaire:** (FCI-T300R/S) Ø 3.15" x 3.23" D, (FCI-T375R/S) Ø 3.86" x 3.35" D **Well Housing:** (See drawings on page 5.)
housing	**Luminaire:** Fully silicone high temperature potted, marine grade, corrosion-resistant, heavy-walled, solid low copper alloy, precision CNC body with with silicone seals. Protected by a captive Nickel Plated Alumium Alloy perimeter flush wall with no visible fasteners for a clean aesthetics. **Well Housing:** High-strength, heavy-walled PVC polymeric material featuring UL 746C f1 UV protection and a UL94 5VA flame rating.
lens	Heavy-gauge, thick, tempered low-iron high-transmission glass lens, IK10 (IEC 62262) impact-resistant. **Optional:** Internal anti-glare optical accessories.
mounting	Pavement, concrete, sand, soil
ingress protection	Luminaire is IP66, IP67, IP68, and IP69K rated (IEC 60529) to withstand water, moisture, and high-pressure jet washdowns. ETL Listed for dry, damp or wet locations. Cabling is anti-syphon (standard) with IP68 waterproof connection systems available as an optional accessory.
impact resistance	IK10 (IEC 62262) impact-resistant for all models and sizes. Heavy-Duty walk over compliant up to 1000 kg (approximately 2,204 lbs).
finish	Housing is chemically cleaned, e-coated, and processed through a 7-stage pretreatment wash before application of UV-resistant, super-durable polyester powder coat at a minimum 18 µm dry-film thickness. Finish withstands a minimum 5,000 hour salt spray test per ASTM B117 and complies with AAMA 2604 and Florida requirements for superior corrosion resistance and weatherability.

PERFORMANCE

color	2700K, 3000K, 3500K, 4000K - 93 CRI (standard)
lumen output	120 lm - 170 lm
beam spread	**NWIN:** Narrow Window Optic (8-10° x 100-110°) or **WWIN:** Wide Window Optic (12-15° x 100-110°) **Note:** Beam angle options vary by size, see IES files for specific beam angles.
lumen maintenance	L70 > 100,000 hours
operating temperature	-22°F to 122°F (-30°C to 50°C)
warranty	5-Year limited warranty

ELECTRICAL

input voltage	24 VDC, **Optional:** UNV (120 - 277 VAC) (includes well housing driver)
power consumption	5W - 7W
power supply	Well housing integral for UNV models (IP67 Rated - see installation instructions). Remote driver options for 24VDC models (order separately - see DRIVER section).
certification	ETL
standards	UL1598 / CSA C22.2 No. 250.0 - Class I / IES LM-79 / LM-80
dimming	Both 24 VDC with REMOTE POWER and UNV Models are Tri-Dim (1%, 0-10V, 120 - 277 VAC), (1%, TRIAC & ELV, 120 VAC Only) standard.
cabling	Optional direct burial cabling options for 24 VDC & UNV available.

Intertek RoHS 2002/95/EC

Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.

US Commercial Lighting Manufacturer Since 1982

© FC Lighting, Inc.
3609 Swenson Ave • St. Charles, IL • 60174 | fclighting.com | 800.900.1730



Ordering Information

ORDERING INFORMATION

	WIN						
MODEL	**SERIES**	**VOLTAGE**	**LIGHT SOURCE**	**COLOR**	**POWER (Typical)**	**OPTICS (Typical)**	**DIMMING**
FCI-T300R 3.00" (80mm) Round					**05W*** 5W (100 Lumens)		
FCI-T375R 3.75" (98mm) Round					**07W** 7W (150 Lumens)		
FCI-T300S 3.00" (80mm) Square					**05W*** 5W (100 Lumens)		
FCI-T375S 3.75" (98mm) Square					**07W** 7W (150 Lumens)		
	WIN Window Optic	**24VDC** 24 VDC	**LED** SMD LED Discrete	**927** 93 CRI, 2700K		**NWIN** Narrow Window Optic (8-10° x 100-110°)	No Dimming (On / Off)
		UNV 120 - 277 VAC		**930** 93 CRI, 3000K		**WWIN**[1] Wide Window Optic (12-15° x 100-110°)	**TD**** Tri-Dim (1%, 0-10V, 120 - 277 VAC), (1%, TRIAC & ELV, 120 VAC Only)
				935 93 CRI, 3500K		[1]**WWIN** *is only available for FCI-T375R & FCI-T375S models.*	
				940 93 CRI, 4000K			

***Note:** *Remote drivers require a minimum of 6W for startup, i.e. two 5W units minimum. See page 3 for driver specifications.*

****Note:** *TD Option with 24VDC requires REMOTE 24VDC POWER Options. Leave blank if no UNV or REMOTE 24VDC is selected, function will be no dimming (ON/OFF).*

Note: *Lumen output typical based on 940 color & NWIN optic, see IES files for complete details.*

Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.



Ordering Information

DRIVERS

INTERIOR - REMOTE 24VDC POWER OPTIONS – Dry, Damp, Wet Location UL Listed
Dimming TD Standard - Tri-Dim (1%, 0-10V, 120 - 277 VAC), (1%, TRIAC & ELV, 120 VAC Only)

_____ **DRR-UNV-24VDC-30W-TD**

_____ **DRR-UNV-24VDC-60W-TD**

_____ **DRR-UNV-24VDC-96W-TD**

IMPORTANT: Remote power supplies must not exceed 80% capacity to prevent overheating and voltage drop.
(Power Supply Wattage × 0.80) ÷ Luminaire Wattage = Maximum Luminaires. (Example: (96W × 0.80) ÷ 5W = 15 luminaires max, rounded down).

EXTERIOR - REMOTE 24VDC POWER OPTIONS – IP66, IP67, IP69 UL Listed
Dimming TD Standard - Tri-Dim (1%, 0-10V, 120 - 277 VAC), (1%, TRIAC & ELV, 120 VAC Only)

_____ **DRX-UNV-24VDC-30W-TD**

_____ **DRX-UNV-24VDC-60W-TD**

_____ **DRX-UNV-24VDC-96W-TD**

IMPORTANT: Remote power supplies must not exceed 80% capacity to prevent overheating and voltage drop.
(Power Supply Wattage × 0.80) ÷ Luminaire Wattage = Maximum Luminaires. (Example: (96W × 0.80) ÷ 5W = 15 luminaires max, rounded down).

ACCESSORIES *(Order separately. Indicate the quantity needed for each item. See page 4 for wiring chart and illustration.)*

_____ **E62902-XX** 18AWG 2C UL DIR BUR CABLE (for 24VDC Option) (XX provide feet in length)

_____ **E62905-XX** 18AWG 5C UL DIR BUR CABLE (for UNV Option) (XX provide feet in length)

_____ **ES1** WATERPROOF WIRE NUTS IN BAG (5PCS). SOLD BY THE BAG. (Qty 1 = 1 Bag). (See wiring chart and illustration section.)

_____ **EW-P20-2P** 24VDC IP68 2-WAY CONNECTOR (only for 24VDC)

_____ **EW-P20T-2P** 24VDC IP68 3-WAY CONNECTOR (only for 24VDC)

_____ **FCI-T-ADJ-TOOL** FCI-T-ADJ ADJUSTABLE TOOL (only for FCI-T-ADJ Models)

_____ **FCI-T-SUCTION** FCI-T-ADJ SUCTION CUP TOOL (for removal/adjustments)

_____ **FCI-T-SUCTION-SMALL** FCI-T-SUCTION CUP TOOL - SMALL for FCI-T175R/S Models (for removal/adjustments)

Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.
© FC Lighting, Inc.



Wiring Information

WIRING CHART AND ILLUSTRATION

MAXIMUM WIRING DISTANCE (Feet)					
WIRE SIZE	10AWG (5.6mm²)	12AWG (3.3mm²)	14AWG (2.0mm²)	16AWG (1.3mm²)	18AWG (0.78mm²)
UNV (120 - 277 VAC)	357	210	137	85	54
30W (24VDC)	480	282	185	114	73
60W (24VDC)	300	176	115	71	45
100W (24VDC)	120	71	46	29	18





Note: *See installation instructions for full details.*

Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.
© FC Lighting, Inc.



Dimensions

PRODUCT DIMENSIONS - STANDARD PRODUCT

Marine grade aluminum with nickel plated alloy construction.

FCI-T300R/S



FCI-T375R/S



MOUNTING - *well housing included, one per luminaire*

French drain required for proper installation, see installation instructions.

FCI-T300R/S (Square Models have Square Nickel Plated Alloy Insert)



FCI-T375R/S (Square Models have Square Nickel Plated Alloy Insert)



Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.
© FC Lighting, Inc.



Photometry

OPTICAL DISTRIBUTION - See IES files for complete details.







Due to continuous development and improvements, specifications are subject to change without notice.
Product use certifies agreement to FC Lighting, Inc. terms and conditions.

© FC Lighting, Inc.