

FCW8051 - INSTALLATION INSTRUCTIONS

CAUTION: BEFORE CONNECTING THE FIXTURE TO A POWER SUPPLY, MAKE SURE THE POWER IS SWITCHED OFF.



FC
LIGHTING

t 800.900.1730 f 630.889.8106
3609 Swenson Ave. St. Charles, IL 60174

DETAILED ILLUSTRATION

GENERAL:

1. Before starting the installation, make sure all electricity has been turned off and electrical breaker has been locked out and tagged out.
2. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
3. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur.

INSTALLATION:

- 1) Fixture Housing supplied has raised posts and screws for mounting both reflector and fixture face assemblies in place. Remove lamping components if necessary to mount Fixture Housing to surface.
- 2) Mount fixture to J-Box or wall.

NOTE: Ensure that Fixture is level before finally tightening. You can add additional anchors to back of Fixture Housing if needed.

- 3) Make power supply connections by bringing power supply wires through provided holes.

NOTE: Make all electrical connections in accordance with local codes, ordinances and NEC (National Electrical Code).

4. Replace component tray into Housing if needed.
5. Replace Gasket, Lens & Faceplate, taking care to evenly tighten screws to create a proper moisture seal.
6. Installer **MUST** add a bead of silicone where the back edge of the Fixture meets the Mounting Surface to avoid water seepage. Failure to do so may void any warranty.

IMPORTANT: All FC|SSL products can be cleaned with non-abrasive and chemical free agents. Use a soft cloth with mild detergent on exterior only.

